



コメント: f=1.5mm F1.4 レンズ

光度計

モデル: U-4000形分光光度計

シリアル No.:

ROM Ver.: 5111 03

装置条件

測定モード: 波長スキャン  
 データモード: %T  
 開始: 1000.00 nm  
 終了: 400.00 nm  
 スキャンスピード: 300(750) nm/min  
 サンプル間隔: 1.00 nm  
 スリット: 5.00 nm  
 補助電圧: 自動制御  
 光源切換モード: 自動切換  
 光源切換波長: 340.00 nm  
 ベースライン設定: ユーザ 1  
 高分解能測定: Off

— 近赤外 —

スリット: 自動制御  
 PbS感度: 1  
 検知器切換補正: 補正あり  
 検知器切換波長: 850 nm

セル長: 10.0 mm

データリスト

nm	%T	nm	%T	nm	%T
1000.00	57.0	998.00	56.9	996.00	56.9
994.00	56.9	992.00	56.8	990.00	57.7
988.00	58.5	986.00	58.7	984.00	58.8
982.00	59.3	980.00	60.0	978.00	60.4
976.00	60.8	974.00	61.6	972.00	61.7
970.00	61.5	968.00	61.9	966.00	62.7
964.00	63.4	962.00	63.9	960.00	64.0
958.00	64.3	956.00	64.9	954.00	65.3
952.00	65.8	950.00	65.7	948.00	66.2
946.00	66.7	944.00	67.0	942.00	67.4
940.00	67.7	938.00	68.2	936.00	68.9
934.00	69.4	932.00	69.6	930.00	69.5
928.00	69.8	926.00	70.1	924.00	70.0
922.00	70.9	920.00	71.7	918.00	72.3
916.00	71.7	914.00	71.8	912.00	72.8
910.00	73.7	908.00	74.7	906.00	75.0
904.00	74.8	902.00	75.0	900.00	74.8
898.00	75.6	896.00	76.2	894.00	76.1
892.00	76.1	890.00	76.6	888.00	77.5
886.00	78.3	884.00	78.3	882.00	78.4
880.00	79.1	878.00	79.7	876.00	80.8
874.00	81.5	872.00	82.3	870.00	83.2
868.00	83.5	866.00	83.6	864.00	83.5
862.00	84.1	860.00	85.0	858.00	85.7
856.00	86.2	854.00	85.5	852.00	85.3
850.00	85.5	848.00	85.8	846.00	85.9
844.00	85.9	842.00	86.5	840.00	87.0
838.00	87.1	836.00	87.0	834.00	86.7
832.00	86.7	830.00	86.4	828.00	86.6
826.00	86.9	824.00	86.5	822.00	86.4
820.00	86.3	818.00	86.6	816.00	86.6
814.00	86.6	812.00	86.9	810.00	87.1
808.00	87.0	806.00	86.9	804.00	86.9
802.00	86.7	800.00	86.4	798.00	86.4
796.00	86.8	794.00	87.3	792.00	87.2
790.00	86.8	788.00	86.5	786.00	86.5
784.00	86.8	782.00	87.0	780.00	86.8
778.00	86.5	776.00	86.1	774.00	86.0
772.00	86.2	770.00	86.2	768.00	86.0
766.00	85.6	764.00	85.6	762.00	85.6
760.00	85.5	758.00	85.2	756.00	85.0
754.00	84.9	752.00	84.8	750.00	84.8
748.00	84.5	746.00	84.4	744.00	84.3
742.00	84.5	740.00	84.5	738.00	84.4
736.00	84.4	734.00	84.5	732.00	84.6
730.00	84.5	728.00	84.4	726.00	84.2
724.00	84.0	722.00	83.9	720.00	83.8
718.00	83.7	716.00	83.6	714.00	83.7
712.00	83.7	710.00	83.6	708.00	83.3
706.00	83.1	704.00	83.2	702.00	83.2
700.00	83.3	698.00	83.1	696.00	82.9
694.00	82.8	692.00	82.7	690.00	82.7
688.00	82.6	686.00	82.4	684.00	82.4
682.00	82.5	680.00	82.7	678.00	82.7
676.00	82.7	674.00	82.7	672.00	82.7
670.00	82.8	668.00	82.8	666.00	82.9
664.00	83.0	662.00	83.2	660.00	83.4
658.00	83.7	656.00	83.9	654.00	83.8
652.00	83.8	650.00	83.9	648.00	84.2
646.00	84.4	644.00	84.4	642.00	84.3
640.00	84.4	638.00	84.4	636.00	84.6
634.00	84.7	632.00	85.0	630.00	85.1
628.00	85.2	626.00	85.5	624.00	85.8
622.00	86.0	620.00	86.2	618.00	86.3
616.00	86.4	614.00	86.5	612.00	86.6
610.00	86.7	608.00	86.6	606.00	86.6
604.00	86.6	602.00	86.7	600.00	86.8
598.00	87.1	596.00	87.2	594.00	87.5
592.00	87.5	590.00	87.5	588.00	87.5
586.00	87.7	584.00	87.9	582.00	88.0
580.00	88.1	578.00	88.2	576.00	88.2
574.00	88.3	572.00	88.4	570.00	88.3
568.00	88.0	566.00	87.6	564.00	87.5

nm	%T	nm	%T	nm	%T
562.00	87.5	560.00	87.5	558.00	87.4
556.00	87.3	554.00	87.3	552.00	87.4
550.00	87.3	548.00	87.2	546.00	86.9
544.00	86.7	542.00	86.6	540.00	86.4
538.00	86.2	536.00	86.0	534.00	85.5
532.00	85.0	530.00	84.5	528.00	84.4
526.00	84.4	524.00	84.0	522.00	83.7
520.00	83.4	518.00	83.2	516.00	83.0
514.00	82.8	512.00	82.5	510.00	82.3
508.00	82.1	506.00	81.6	504.00	81.1
502.00	80.5	500.00	80.2	498.00	80.0
496.00	79.9	494.00	79.6	492.00	79.2
490.00	79.1	488.00	78.9	486.00	78.8
484.00	78.6	482.00	78.5	480.00	78.5
478.00	78.3	476.00	77.9	474.00	77.7
472.00	77.6	470.00	77.6	468.00	77.9
466.00	77.9	464.00	77.9	462.00	78.1
460.00	78.5	458.00	78.9	456.00	78.5
454.00	78.3	452.00	78.4	450.00	78.8
448.00	79.1	446.00	79.1	444.00	79.4
442.00	79.8	440.00	80.0	438.00	80.1
436.00	80.2	434.00	80.3	432.00	80.1
430.00	79.9	428.00	79.7	426.00	79.1
424.00	79.0	422.00	78.6	420.00	77.9
418.00	77.0	416.00	76.0	414.00	75.0
412.00	73.2	410.00	71.1	408.00	69.1
406.00	67.0	404.00	64.7	402.00	61.9
400.00	59.8				